



# TOWERLIFT RANGE





## Introduction

The international recognition achieved by VMB Towerlifts is the result of a culture of continuous hard work year after year: to develop, manufacture and supply products for professional use, offering the highest standards of reliability, performance and strength.

VMB towerlifts have been designed for the professional user who demands a quality, trustworthy and practical product which guarantees the utmost security at work. The development, manufacture and quality controls are carried out by fully trained staff and every single piece or component, as well as the final product, undergoes rigorous quality and strength control.

Since we started manufacturing our first towerlifts in 1986, we have been continuously employing innovative materials, mechanisms and manufacturing processes in order to adapt our product range to the ever-increasing demands of the market.

Our towerlifts are fitted with the ALS Auto Lock Security System patented by VMB in the European Union and the U.S.A. The ALS system guarantees that all sections stay fixed at which ever height and makes it impossible for the load to collapse.

VMB Towerlifts are regarded and recognised worldwide for their quality and security and nowadays the brand has become synonymous with the product.

### There are five different series of VMB Towerlifts:

**CLASSIC SERIES.** *Traditional towerlifts with a load capacity up to 100 Kg. They are provided with standard security locks.*

**PRO SERIES.** *Towerlifts with a load capacity superior to 100 Kg, 200 Kg and a maximum load capacity of 230 Kg. All the towerlifts of this series are provided with the exclusive ALS Automatic Lock Security system patented by VMB.*

**TL SERIES.** *Front load HEAVY DUTY towerlifts. They can load from the ground from 200 Kg to 320 Kg, maximum load capacity. They are provided with the exclusive ALS retentor security system especially designed for this kind of towerlifts, Pat.Pen. 200501056. They are made of aluminium profiles.*

**TRUSS TOWER SERIES.** *Ground Support and truss towers with a load capacity of 500 Kg, 1000 Kg and 2000 Kg.*

**PIRAM.** *Especially designed to fly line arrays up to 1000 Kg/10 m.*



TOWERLIFT TE-034	PAG. 04
TOWERLIFT TE-06	PAG. 05
<hr/>	
TOWERLIFT TE-064P	PAG. 06
TOWERLIFT TE-071P	PAG. 07
TOWERLIFT TE-074P	PAG. 08
TOWERLIFT TE-076P	PAG. 09
CLASSIC ACCESSORIES / PRO	PAG. 10
<hr/>	
TOWERLIFT TL-054	PAG. 12
TOWERLIFT TL-055	PAG. 13
TOWERLIFT TL-056	PAG. 14
TOWERLIFT TL-072	PAG. 15
TOWERLIFT TL-075C	PAG. 16
TOWERLIFT TL-078	PAG. 17
TOWERLIFT TL-A220	PAG. 18
TOWERLIFT TL-A320	PAG. 19
TL ACCESSORIES	PAG. 20
<hr/>	
TE-30	PAG. 22
GS-30	PAG. 23
GS-40	PAG. 24
GS ACCESSORIES	PAG. 25
<hr/>	
PIRAM	PAG. 26
<hr/>	
WHY VMB TOWERLIFTS?	PAG. 28
<hr/>	
TECHNICAL SPECIFICATIONS	PAG. 30



classic series 

# TE-034

The TE-034 is a telescopic Towerlift, designed to be used in every kind of small event such as shows, presentations and all other industrial uses.

Once folded, it is compact enough to fit in the boot of a car.

The TE-034 Towerlift is built with three steel telescopic profiles operated with a cable through a manual winch with a disc brake.

Two security locks block the sections of the Towerlift when in working position to avoid the cable supporting the load when in operation and so guarantees a fixed position.

It has four extendable and adjustable legs with non-slip feet.

Once the towerlift is folded, a handle makes the transport in horizontal position easier.

The adjustable supports PSU-06 and PSA-01 make it possible to lift any kind of truss. Different accessories and supports are also available to lift any other loads. See page 10.

Available in silver or black.



## ▶▶ TECHNICAL SPECIFICATIONS

Maximum height	3,8 m
Maximum load	100 Kg
Work surface	1,5 x 1,5 m
Folded height	1,26 m
Weight	21 Kg
Winch	340 Kg
Adaptor	∅ 35 mm (PSU-06/PSA-01)

## SAFETY CATCH



## CERTIFICATIONS

BGV C1 (GUV-VC1)  
CE 89/392 EWG





classic series

# TE-06

The TE-06 is a telescopic Towerlift, designed to be used in shows, presentations and many different industrial uses.

The TE-06 Towerlift is built with three steel telescopic profiles operated with a cable through a manual winch with a disc brake.

Two security locks block the sections of the Towerlift when in working position to avoid the cable supporting the load when in operation and so guarantees a fixed position.

It has four stabilising legs that come with adjustable disc feet with non-slip injected rubber. Stabilising legs can be removed and placed in special compartments on the base. A handle makes the transport easier.

A spirit level helps to maintain the vertical position of the Towerlift.

The adjustable supports PSU-06 and PSA-01 make it possible to lift any kind of truss. Different accessories and supports are also available to lift any other loads. See page 10.

Available in silver or black.



## TECHNICAL SPECIFICATIONS

SAFETY CATCH



Maximum height	5 m
Maximum load	100 Kg
Work surface	2 x 2 m
Folded height	1,90 m
Weight	32 Kg
Winch	340 Kg
Adaptor	∅ 35 mm (PSU-06/PSA-01)

## CERTIFICATIONS

BGV C1 (GUV-VC1)  
CE 89/392 EWG



pro series 

# TE-064<sup>PRO</sup>

The TE-064 Pro is a telescopic Towerlift for heavy loads, designed for professional use and for any show where strength, security and ease of use are required.

The four sections of the TE-064 Pro are operated with a steel cable through a manual winch with a disc brake. The sections remain automatically fixed to the required height by the locks of the exclusive ALS Auto Lock Security system patented by VMB. The ALS system fixes the sections to the required height, blocking the Towerlift and making it impossible for the load to fall. It guarantees complete working security on stage.

It has four stabilising legs that can be removed and come with adjustable disc feet, swivel wheels and a spirit level that helps to maintain the vertical position of the Towerlift.

With the Towerlift folded and the legs back in their compartments, it forms a compact block which makes it easy to manoeuvre around thanks to the swivel wheels of the base.

The adjustable supports PSU-06 and PSA-01 make it possible to lift any kind of truss. Different accessories and supports are also available to lift any other loads. See page 10.

TE-064 Pro Towerlifts are available in satin black TE-064PB or in Standard silver zinc TE-064PS.



## ▶▶ TECHNICAL SPECIFICATIONS

Maximum height	5,35 m
Maximum load	100 Kg
Security	ALS
Work surface	2 x 2 m
Folded height	1,72 m
Weight	41 Kg
Winch	340 Kg
Adaptor	∅ 35 mm (PSU-06/PSA-01)

ALS (auto-lock security)



## CERTIFICATIONS

BGV C1 (GUV-VC1)  
CE 89/392 EWG

CE





pro series

# TE-071P

RH-1



The TE-071 Pro is a telescopic Towerlift for heavy loads, designed for professional use with a maximum load capacity of 200 kg and a good manoeuvrability thanks to its adjusted transport weight.

The four sections of the TE-071 Pro are operated with a steel cable through a manual winch with a disc brake.

The sections remain automatically fixed to required height by the locks of the exclusive ALS Auto Lock Security system patented by VMB. The ALS system fixes the sections to the required height, blocking the Towerlift and avoiding the cable to support the load when operating. It makes it impossible for the load to fall and guarantees complete working security.

It has four stabilising legs that can be removed and come with adjustable disc feet, swivel wheels and a spirit level that helps to maintain the vertical position of the Towerlift.

Each section is fitted with a manual screw so the user can control which section rises first.

With the Towerlift folded and the legs back in their compartments, it forms a compact block which makes it easy to manoeuvre around thanks to the swivel wheels of the base.

The adjustable supports PSU-06 and PSA-01 make it possible to lift any kind of truss. A wheel kit (RH-1) is also available to transport the towerlift horizontally. Different accessories and supports are also available to lift any other loads. See page 10.

TE-071 Pro Towerlifts are available in satin black TE-071P or in Standard silver zinc TE-071PS.

## ▶▶ TECHNICAL SPECIFICATIONS

Maximum height	5,35 m
Maximum load	200 Kg
Security	ALS
Work surface	2,1 x 2,1 m
Folded height	1,73 m
Weight	71 Kg
Winch	500 Kg
Adaptor	∅ 35 mm (PSU-06/PSA-01)

ALS (auto-lock security)



## CERTIFICATIONS

BGV C1 (GUV-VC1)  
CE 89/392 EWG



pro series 

# TE-074P

The TE-074 Pro is a telescopic Towerlift for heavy loads, designed for professional uses with a maximum load capacity of 230 kg.

The four sections of the TE-071 Pro are operated with a steel cable through a manual winch with a disc brake.

The sections remain automatically fixed to required height by the locks of the exclusive ALS Auto Lock Security system patented by VMB. The ALS system fixes the sections to the required height, blocking the Towerlift and avoiding the cable to support the load when operating. It makes it impossible for the load to fall and guarantees complete working security.

It has four stabilising legs that can be removed and come with adjustable disc feet, swivel wheels and a spirit level that helps to maintain the vertical position of the Towerlift.

Each section is fitted with a manual screw so the user can control which section rises first.

With the Towerlift folded and the legs back in their compartments, it forms a compact block which makes it easy to manoeuvre around thanks to the swivel wheels of the base.

The adjustable supports PSU-074 and PSA-02 make it possible to lift any kind of truss. A wheel kit (RH-1) is also available to transport the towerlift horizontally. Different accessories and supports are also available to lift any other loads. See page 10.

TE-074 Pro Towerlifts are available in satin black TE-074P or in Standard silver zinc TE-074PS.



## ▶▶ TECHNICAL SPECIFICATIONS

Maximum height	5,35 m
Maximum load	230 Kg
Security	ALS
Work surface	2,1 x 2,1 m
Folded height	1,74 m
Weight	91 Kg
Winch	650 Kg
Adaptor	∅ 55 mm (PSU-074/PSA-02)

ALS (auto-lock security)



## CERTIFICATIONS

BGV C1 (GUV-VC1)  
CE 89/392 EWG

CE





pro series

# TE-076P



The TE-076 Pro is a telescopic Towerlift for heavy loads, designed for professional uses where a height of more than 6 m is required.

The five sections of the TE-076 Pro are operated with a steel cable through a manual winch with a disc brake.

The sections remain automatically fixed to required height by the locks of the exclusive ALS Auto Lock Security system patented by VMB. The ALS system fixes the sections to the required height, blocking the Towerlift and avoiding the cable to support the load when operating. It makes it impossible for the load to fall and guarantees complete working security.

It has four stabilising legs that can be removed and come with disc feet, swivel wheels and a spirit level that helps to maintain the vertical position of the Towerlift.

Each section is fitted with a manual screw so the user can control which section rises first.

With the Towerlift folded and the legs back in their compartments, it forms a compact block which makes it easy to manoeuvre around thanks to the swivel wheels of the base.

The adjustable supports PSU-06 and PSA-01 make it possible to lift any kind of truss. A wheel kit (RH-1) is also available to transport the towerlift horizontally. Different accessories and supports are also available to lift any other loads. See page 10.

TE-076 Pro Towerlifts are available in satin black TE-076P or in Standard silver zinc TE-076PS.

## TECHNICAL SPECIFICATIONS

Maximum height	6,5 m
Maximum load	200 Kg
Security	ALS
Work surface	2,4 x 2,4 m
Folded height	1,83 m
Weight	95 Kg
Winch	650 Kg
Adaptor	∅ 35 mm (PSU-06/PSA-01)

ALS (auto-lock security)



## CERTIFICATIONS

BGV C1 (GUV-VC1)  
CE 89/392 EWG



### PSU-06

Adjustable support for truss, with U-piece and pin.  
Suitable for towerlifts with insertion of 35 mm.



### BT-061

Support for lights bar. Suitable for towerlifts with  
insertion of 35 mm.



### PSA-01

Adjustable support for truss, with tilting aircraft grips.  
For towerlifts with insertion of 35 mm.



### PSA-02

Adjustable support for truss, with tilting aircraft grips.  
For towerlifts with insertion of 55 mm.



### PSU-074

TE-074Pro adjustable support for truss, with U-piece  
and pin. Insertion of 55 mm.

### BT-071

TE-074Pro support for lights bar. Insertion of 55 mm.



### BT-072

TE-074Pro support for two lights bar.  
Insertion of 55 mm.



### BT-062

Support for two lights bars. Suitable for  
all towerlifts with insertion of 35 mm.



## accessories



**BT-06**

Support bar with length of 1.89 m. Suitable for all towerlifts with insertion of 35 mm.



**BT-07**

TE-074Pro support bar with length of 1.89 m. Insertion of 55 mm.




**SPG-3529**

Adaptor for Spigot with insertion of 29 mm. Suitable for towerlift insertion of 35 mm.

**SPG-5529**

TE-074Pro adaptor for Spigot with insertion of 29 mm. Towerlift insertion of 55 mm.



**AT-01**

Aircraft, suitable for towerlifts with insertion of 35 mm.



**AT-02**

Aircraft, suitable for towerlifts with insertion of 55 mm.



**PSD-01**

Flat truss support for towerlifts with insertion of 35 mm.



**PSB-01**

Plate support for towerlifts with insertion of 35 mm.



**RH-1**

Transport kit for Pro series towerlifts.



tl series 

# TL-054

This front load towerlift can lift 220 kg from the ground. It is built with four aluminium profiles and a lifting carriage that are guided along by nylon rollers. The sections are operated with a steel cable through a manual winch with a disc brake.

Each one of the profiles is secured with an automatic inertia lock ILS that will lock the profile in a fixed and stable position in case the cable breaks.

The aluminium sections are fixed on a solid steel base provided with swivel wheels for ease of transport. The base also has a special compartment for the four stabilising legs that are provided with adjustable mounting plates and a spirit level that helps to maintain the vertical position of the towerlift. The load is lifted on two steel arms that are fixed on the lifting carriage.

The lifting carriage benefits from an automatic inertia lock that blocks the lifting carriage in a fixed and stable position in case the cable breaks.

The towerlift can also be transported in a horizontal position thanks to the RH-2 wheels optional kit.

See page 20 for all accessories including Line Array flying options.

They are available in natural aluminium colour or in satin black.



## ▶▶ TECHNICAL SPECIFICATIONS

Maximum height	5,45 m
Maximum load	220 Kg
Security	ILS
Work surface	2 x 2 m
Folded height	1,70 m
Weight	87 Kg
Winch	900 Kg
Load support	Forks

ILS (Inertia- Lock-Security)



## CERTIFICATIONS

BGV C1 (GUV-VC1)  
CE 89/392 EWG

CE





**MIB** tl series  
**TL-055**

This front load towerlift can lift 220 kg from the ground. It is built with three aluminium profiles and a lifting carriage that are guided along by nylon rollers. The sections are operated with a steel cable through a manual winch with a disc brake.

Each one of the profiles is secured with an automatic inertia lock ILS that will lock the profile in a fixed and stable position in case the cable breaks.

The aluminium sections are fixed on a solid steel base provided with swivel wheels for ease of transport. The base also has a special compartment for the four stabilising legs that are provided with adjustable mounting plates and a spirit level that helps to maintain the vertical position of the towerlift. The load is lifted on two steel arms that are fixed on the lifting carriage.

The lifting carriage benefits from an automatic inertia lock that blocks the lifting carriage in a fixed and stable position in case the cable breaks.

See page 20 for all accessories including Line Array flying options.

The towerlift can also be transported in a horizontal position thanks to the RH-2 wheels optional kit are available in natural aluminium colour or in satin black.

▷▷ TECHNICAL SPECIFICATIONS

Maximum height	5,1 m
Maximum load	220 Kg
Security	ILS
Work surface	2 x 2 m
Folded height	1,98 m
Weight	88,5 Kg
Winch	900 Kg
Load support	Forks

ILS (Inertia- Lock- Security)



CERTIFICATIONS

BGV C1 (GUV-VC1)  
CE 89/392 EWG



tl series 

# TL-056

This front load towerlift can lift 200 kg from the ground. It is built with three aluminium profiles and a lifting carriage that are guided along by nylon rollers. The sections are operated with a steel cable through a manual winch with a disc brake.

Each one of the profiles is secured with an automatic inertia lock ILS that will lock the profile in a fixed and stable position in case the cable breaks.

The aluminium sections are fixed on a solid steel base provided with swivel wheels for ease of transport. The base also has a special compartment for the four stabilising legs that are provided with adjustable mounting plates and a spirit level that helps to maintain the vertical position of the towerlift. The load is lifted on two steel arms that are fixed on the lifting carriage.

The lifting carriage benefits from an automatic inertia lock that blocks the lifting carriage in a fixed and stable position in case the cable breaks.

See page 20 for all accessories including Line Array flying options.

The towerlift can also be transported in a horizontal position thanks to the RH-2 wheels optional kit are available in natural aluminium colour or in satin black.



### ▶▶ TECHNICAL SPECIFICATIONS

Maximum height	6,5 m
Maximum load	200 Kg
Security	ILS
Work surface	2 x 2 m
Folded height	1,98 m
Weight	94,5 Kg
Winch	900 Kg
Load support	Forks

ILS (Inertia-Lock-Security)



### CERTIFICATIONS

BGV C1 (GUV-VC1)  
CE 89/392 EWG





tl series

# TL-072

This front load HEAVY DUTY Towerlift can lift 240 kg from the ground.

It is built with four aluminium profiles and a lifting carriage that are guided along by nylon rollers. The sections are operated with a steel cable through a manual winch with a disc brake.

Sections raise one after another and remain fixed in the required position thanks to the exclusive ALS security system especially designed for this kind of towerlifts, Pat. Pen. 200501056. This security system blocks the sections of the towerlift automatically to avoid the cable supporting the load when in operation. This makes it impossible for the load to fall.

The aluminium sections are fixed on a solid steel base provided with swivel wheels for ease of transport. The base also has a special compartment for the four stabilising legs that are provided with adjustable mounting plates and a spirit level that helps to maintain the vertical position of the Towerlift. The load is lifted on two steel arms that are fixed on the lifting carriage.

The lifting carriage benefits from two security systems: the ALS system and an automatic inertia lock that blocks the lifting carriage in a fixed and stable position in case the cable breaks.

The Towerlift can also be transported in a horizontal position thanks to the RH-3 wheels optional kit.

They are available in natural aluminium colour or in B satin black (made to order).



## ▶▶ TECHNICAL SPECIFICATIONS

Maximum height	6,5 m
Maximum load	240 Kg
Security	ALS
Work surface	2,2 x 2,2 m
Folded height	1,98 m
Weight	114 Kg
Winch	900 Kg
Load support	Forks

ALS (auto-lock security)



## CERTIFICATIONS

BGV C1 (GUV-VC1)  
CE 89/392 EWG



tl series   
**TL-075c**

This front load HEAVY DUTY Towerlift can lift 300 kg from the ground.

It is built with four aluminium profiles and a lifting carriage that are guided along by nylon rollers. The sections are operated with a steel cable through a manual winch with a disc brake. Sections raise one after another and remain fixed in the required position thanks to the exclusive ALS security system especially designed for this kind of towerlifts, Pat. Pen. 200501056. This security system blocks the sections of the towerlift automatically, to avoid the cable supporting the load when in operation. This makes it impossible for the load to fall.

The aluminium sections are fixed on a solid steel base provided with swivel wheels for ease of transport. The base also has a special compartment for the four stabilising legs that are provided with adjustable mounting plates and a spirit level that helps to maintain the vertical position of the Towerlift. The load is lifted on two steel arms that are fixed on the lifting carriage.

The lifting carriage benefits from two security systems: the ALS system and an automatic inertia lock that blocks the lifting carriage in a fixed and stable position in case the cable breaks.

They are available in natural aluminium colour or in B satin black (made to order). The Towerlift can also be transported in a horizontal position thanks to the RH-4 wheels optional kit.



▷▷ TECHNICAL SPECIFICATIONS

Maximum height	6,5 m
Maximum load	300 Kg
Security	ALS
Work surface	2,2 x 2,2 m
Folded height	1,98 m
Weight	179 Kg
Winch	1200 Kg
Load support	Brazos

ALS (auto-lock security)



CERTIFICATIONS

BGV C1 (GUV-VC1)  
 CE 89/392 EWG



# TL-078



The TL-078 is a front load HEAVY DUTY Towerlift designed for professional uses where a height up to 8 m. is required.

It is built with five aluminium profiles and a lifting carriage that are guided along by nylon rollers.

The sections are operated with a steel cable through a manual winch with a disc brake. Sections raise one after another and remain fixed in the required position thanks to the exclusive ALS security system especially designed for this kind of towerlifts, Pat. Pen. 200501056. This security system blocks the sections of the towerlift automatically, to avoid the cable to supporting the load when in operation. This makes it impossible for the load to fall, avoiding the cable to hold the load up when operating. It makes it impossible for the load to fall.

The aluminium sections are fixed on a solid steel base provided with swivel wheels for ease of transport. The base also has a special compartment for the four stabilising legs that are provided with adjustable mounting plates and a spirit level that helps to maintain the vertical position of the Towerlift. The load is lifted on two steel arms that are fixed on the lifting carriage.

The lifting carriage benefits from two security systems: the ALS system and an automatic inertia lock that blocks the lifting carriage in a fixed and stable position in case the cable breaks.

They are available in natural aluminium colour or in B satin black (made to order). The Towerlift can also be transported in a horizontal position thanks to the RH-4 wheels optional kit.

## TECHNICAL SPECIFICATIONS

Altura m xima	8 m
Carga m xima	280 Kg
Seguridad	ALS
Area de trabajo	2,2 x 2,2 m
Altura plegada	1,98 m
Peso	203 Kg
Winch	1200 Kg
Soporte carga	Brazos

ALS (auto-lock security)



## CERTIFICATIONS

BGV C1 (GUV-VC1)  
CE 89/392 EWG



tl series



# TL-A220

The TL-A220 is specifically designed for lifting small and medium format Line Arrays to a height of 5.50 m with a maximum weight of 220kg. The towerlift allows the Line Array to be situated at a distance from the lift so as to achieve the required inclination of the cabinets and ensure perfect coverage.

The TL-A220 is designed to offer unprecedented front and lateral stability, guaranteeing fixed and safe positioning of the Line Array

With conventional towerlifts, the maximum load is rapidly reduced the further away from the profile the load is placed. A capacity of 250kg, is reduced to 125kg at 50cm from the towerlift.

The TL-A220 can lift 220kg with the centre of gravity situated at 50cm from the towerlift profile. This means that the front of the Line Array can be at 1 metre from the towerlift

The TL-A220 body is comprised of four aluminium profiles which slide against each other, guided along by nylon rolls. The profiles raise via steel cable through an automatic brake manual winch. They remain automatically blocked and fixed in working position thanks to the ALS security system (Pat. pen 200501056) which guarantees the total security and reliability of the load. Once blocked the towerlift does not rely on the cable for any support.

The detailed design of the towerlift steel base has, for the first time, made it possible to load a Line Array directly next to the towerlift body without the outriggers getting in the way.

The rear support bars as well as the frontal support affirm this towerlifts stability. Never the less, on profile 2, two anchor points are built in to allow the towerlift to be attached to the ground in case the towerlift is used in heavy wind conditions.

The towerlift can be transported vertically or horizontally by mounting the optional RH-2 wheel kit.



## ▶▶ TECHNICAL SPECIFICATIONS

Maximum height	5,5 m
Maximum load	220 Kg (0.5 m advanced)
Security	ALS
Work surface	2,78 x 2,78 m
Folded height	1,72 m
Weight	95 Kg
Winch	900 Kg
Load support	Forks

ALS (auto-lock security)



## CERTIFICATIONS

BGV C1 (GUV-V C1)  
CE 89/392 EWG





tl series

# TL-A320

The TL-A320 is specifically designed for lifting Line Array to a height of 6m with a maximum weight of 320kg. The towerlift allows the Line Array to be situated at a distance from the lift so as to achieve the required inclination of the cabinets and ensure perfect coverage.

The TL-A320 is designed to offer unprecedented front and lateral stability, guaranteeing fixed and safe positioning of the Line Array

With conventional towerlifts, the maximum load is rapidly reduced the further away from the profile the load is placed. A capacity of 300kg, is reduced to 190kg at 50cm from the towerlift.

The TL-A320 can lift 320kg with the centre of gravity situated at 50cm from the towerlift profile. This means that the front of the Line Array can be at 1 metre from the towerlift

The TL-A320 body is comprised of four aluminium profiles which slide against each other, guided along by nylon rolls. The profiles raise via steel cable through an automatic brake manual winch. The profiles lift in order. They also remain automatically blocked and fixed in working position thanks to the ALS security system (Pat. pen 200501056) which guarantees the total security and reliability of the load. Once blocked the towerlift does not rely on the cable for any support.

The detailed design of the towerlift steel base has, for the first time, made it possible to load a Line Array directly next to the towerlift body without the outriggers getting in the way.

The rear support bars as well as the frontal support affirm this towerlifts stability. Never the less, on profile 2, two anchor points are built in to allow the towerlift to be attached to the ground in case the towerlift is used in heavy wind conditions.

The towerlift can be transported vertically or horizontally by mounting the optional RH-4 wheel kit.



## TECHNICAL SPECIFICATIONS

Maximum height	6 m
Maximum load	320 Kg (0.5 m at distance)
Security	ALS
Work surface	2,25 x 2,15 m
Folded height	1,98 m
Weight	184 Kg
Winch	1200 Kg
Load support	Forks

ALS (auto-lock security)



## CERTIFICATIONS

BGV C1 (GUV-VC1)  
CE 89/392 EWG



BC-075

TL series load fork. 0,55 m.



PS-1TR PS-2TR

U piece for transverse or longitudinal load.



RH-2

Transport kit for TL-054, TL-055 and TL-056.



RH-3

Transport kit for TL-072.



RH-4

Transport kit for TL-075C and TL-078.



GS

Shackles with capacity of 500, 1000 and 2000 kg



BC-075L

Long fork for line array systems. 0,75 m.



FAS-01

Special support to lift PA systems with the forks BC-075L.



FAS-02

Special support to lift PA systems with the forks BC-075L.



# TL accessories



gs series 

# TE-30

Truss-Tower with square 30 x 30 cm section and steel lifting carriage operated via manual winch cable. Cushioned by the vertical tower structure it moves via nylon pulleys.

Security system which blocks the lifting carriage automatically in case the cable breaks.

The Tower body is 6082-T6 aluminium and is constructed with tubular sections, 50 mm external diameter for the lifting sections and 16 mm exterior diameter for triangular bars.

The Towerlift is set on a solid steel base with twisting wheels for the transport and 4 stabiliser legs adjustable depending on work surface.



### ▶▶ TECHNICAL SPECIFICATIONS

Maximum height	7 m
Maximum load	750 Kg
Security	ALS
Work surface	2,8 x 2,8 m
Winch	1200 Kg
Structure	Square truss 30 x 30 cm

CE 89/392 EWG





gs series

# GS-30



Truss-Tower with square 30 x 30cm section and steel lifting carriage operated by electric chain motor. Cushioned by the vertical tower structure it moves via nylon pulleys.

The 30 x 30 cm structure is 6082-T6 aluminium and is constructed with tubular sections, 50 mm external diameter with 3.5 mm thickness for the main lifting sections and 26 mm exterior diameter with 3.5 mm thickness for triangular bars

The fixing between sections is carried out with perforated plaques of the same material and fixed with M-16/8.8 screws.

The Towerlift is set on a solid steel base with twisting wheels for the transport and 4 stabiliser legs adjustable depending on work surface.

## ▷▷ TECHNICAL SPECIFICATIONS

Maximum height	12 m
Maximum load	1500 Kg
Elevation	1000 Kg CM hoist
Structure	Square truss 30 x 30 cm
Main bars	50 mm x 3,5 mm
Braces	26 mm x 3,5 mm

CE 89/392 EWG



gs series 

# GS-40

Truss-Tower with square 40 x 40 cm section and steel lifting carriage operated by electric chain motor. Cushioned by the vertical tower structure it moves via nylon pulleys.

The 40 x 40 cm structure is 6082-T6 aluminium and is constructed with tubular sections, 50mm external diameter with 3.5 mm thickness for the main lifting sections and 26 mm exterior diameter with 3.5 mm thickness for triangular bars.

The fixing between sections is carried out with perforated plaques of the same material and fixed with M-16/8.8 screws.

The Towerlift is set on a solid steel base with twisting wheels for the transport and 4 stabiliser legs adjustable depending on work surface.



## ▷▷ TECHNICAL SPECIFICATIONS

Maximum height	14 m
Maximum load	3000 Kg
Elevation	2000 Kg CM hoist
Structure	Square truss 40 x 40 cm
Main bars	50 mm x 3,5 mm
Braces	26 mm x 3,5 mm

CE 89/392 EWG



SV- 52/30

PA wing for Ground Support GS-30. Load capacity 650 Kg. Also available for GS-40.



PCM- 1000

Columbus McKinnon Lodestar chain hoist for 1000 Kg (also available for 2000 Kg)



DC1-L

Direct control Lodestar chain hoist for 1000 Kg (also available for 2000 Kg)



ES1/2TM

Poliester roundsling with capacity of 2000 Kg. Circumference 1 m (other circumferences available)



CMO- 4CM/CMR- 4VC

4 hoists controller, with direct or remote control (other models available up to 12 hoists)




PM- P05

Hand chain hoist for 500 kg (also available for 1 ton and 2 tonnes)



GS

Shackles with capacity of 500, 1000 and 2000 Kg



# accessories

# PIRAM

BY VMB

The PIRAM Fly Array system has been originally designed to fly the VMB Lynx curvilinear array and is one of the best solutions for general Line array PA flying.

This new reliable and safe flying system offers excellent practical specifications: it is easy and quick to install, it takes little room for transport and it can lift up to 1000 kg loads to more than 10 meters high depending on the model.

With this new and original design (registered) VMB engineering is again leading the way.

The PIRAM towerlift responds to the needs of audio industry professionals all over the world and it is probably the best solution to fly line array systems.

PIRAM towerlifts are made entirely of 6082 T-6 aluminium. There are three different types of structures according to the loading capacity.

Standard towerlifts can lift loads to a maximum of 6.2 meters.

Using and assembling sections of 2 m or 3 m, you can reach a maximum 10 m height.


For higher flying system or heavier loads please contact us.

Each flying towerlift is provided with articulated ground base plates for a perfect support and anchor points in their upper part to fix the lift supports.

Equipments can be lifted with an electric hoist or a manual hand chain block with load lifting capacities adequate to each model.



# accessories



PK-1013

Articulated ground base plate



PK-1014

Ground base plate



PK-712

Piram legs union with aircraft fixations.



PK-710/PK-1010

Top head truss piece for PIRAM-750 / 1000

## PIRAM 750

### ▷▷ TECHNICAL SPECIFICATIONS

Maximum load	750 Kg
Maximum height	8 m
Structure	Triangular 25 cm
Base surface	3,22 x 3,22 m
Ground base	Articulated
Material	Al 6082-T6

## PIRAM 1000

### ▷▷ TECHNICAL SPECIFICATIONS

Maximum load	1000 Kg
Maximum height	10 m
Structure	Square 30 cm
Base surface	3,62 x 3,62 m
Ground base	Articulated
Material	Al 6082-T6



Leeds Castle, England.

# why VMB towerlifts?

- ▷▷ "VMB towerlifts represent an original construction and certified quality for affordable price"

***Music Data, Czech Republic***

- ▷▷ "We have used VMB towerlifts in our professional rental for many years. They suit us well, and we trust them from small to big setups"

***Michael Henriksen, Unico Gruppen, Denmark***

- ▷▷ "After buying my VMB TE-074P I have to say that I am more than happy with them. Stable, Strong, Super Security with a great advantage compared with a competitor brand I was using before. The ALS, Auto Lock Security system is wonderful. Thank you for introducing me to VMB towerlifts"

***M Bresset, ALB, France***

- ▷▷ "We would only ever use VMB towerlifts, why would we use anything else? They are the most reliable and ofcourse, the safest on the market and when you are lifting and lowering expensive equipment it is important to have peace of mind"

***Carlos Berlanga, Watussi, Spain***

- ▷▷ "VMB towerlifts are providing me with the flexibility to raise my lights, line array system and my other devices safely and efficiently"

***Mega Kol, Israel'***

- ▷▷ We've been using VMB Towerlifts in our production department for a couple of years now and they've been excellent. Our Towerlifts are workhorses that get used on almost all of our hotel/club touring systems. You take them out of the case, put the truss on, then they go up and when the gig's finished, they come back down and go back into the road case - sounds simple, but they do this EVERY TIME with no problems or breakages (not so with our other/older Winchups). Indeed, we've just sold our winchups to a scrap metal yard and now only have VMB Towerlifts as ground support"

***Neale Mace, Entertainment Installations, Australia***

- ▷▷ "We are using more than 20 VMB Towerlifts. We sold all the other competitor products during the last year and now only use VMB. We have now also bought 4 TL-075C for flying the Lynx Line Array. We are very happy with the big range and the excellent Service from VMB"

***Thomas Wernikowski, Acoustic Sound, Germany***

- ▷▷ "We are really happy with our VMB towerlifts and especially like them because of their Safety and also because they are easy to operate"

***AVAB CAC, Norway***

- ▷▷ "Certainly, The big advantage with VMB towerlifts is the wide range they offer, it helps to be able to choose the right product for specific needs and every kind of installation. A good idea was adding black products which helps us to use them in theaters. The most important thing is quality and security of all VMB products. CE and all other certificates assure us that these are the right products for us"

***Piotr Wojtas, Elwolight, Poland***

- ▷▷ "VMB towerlifts never disappoint me. Even when I was in need to force them to their limits. Then I really loved them"

***George Kastanis, Super Sound, Greece***

- ▷▷ "VMB towerlifts have given us the ability to rig up our sound systems in practically any venue and they really add value to the services we have to offer. Above all they make us look and sound great at all times"

***Warren D'Souza, SOUND.COM, India***

- ▷▷ "We have several VMB towerlifts in our rental stock, in three cities. As Sweden is such a large country they travel a lot and we are very satisfied with their reliability"

***Spectra Stage & Event Technologies, Sweden***

- ▷▷ "I'm really happy with my TL-054 towerlifts and they have been used to install some really big exhibition stands. They enable me to save time. Also, most importantly for me is the quality of service from VMB"

***Thierry Tabarin, PSB Sonorisation, Belgium***





▷▷ "Broadway Finland Oy has trusted VMB's capability and reliability when lifting sound and light equipments in all kind of events. We know that you must have the best quality in use to get everything running well. Our team has over 20 years experience lifting things so we know what we are talking about"

***Jani Pellikka, Broadway, Finland***

▷▷ "What can I say about VMB towerlifts, robust, easy to set up and include a technological security system capable of reinsuring all professionals. They also have an excellent price/quality ratio"

***Richard Pianetti, AUDIO TECHNIQUE, France***

▷▷ "What makes VMB towerlifts so competitive is their multi-purpose, simple use that goes from lifting a simple truss section to ground supporting a full ballroom draping truss system. We have recently ordered around 24 VMB towerlifts for our rental department and are very happy. You can easily store them, roll them to your truck and on site and they support up to 200Kg at 6.5m height"

***Abderrazek Hakimi, TechnoPro, Middle East***

▷▷ "We have more than 30 years of working with Pro light & Sound so when the new VMB Towerlift came on the market we were more than satisfied with its capabilities. The VMB Towerlift proved to be very mobile with the smallest (only 1.7m high) fitting absolutely anywhere. We should not forget to mention the technical capabilities and safety features of the VMB towerlift which displays a variety of options working with lighting, audio and video equipment"

***Jernej Podbešek, SST-d.o.o., Slovenia***

▷▷ "VMB Towerlifts offer Southern African users ultimate rigging flexibility in order to adapt to the growing live event market in the country. The superior engineering, quality and safety backed by excellent technical support and documentation makes VMB the product of choice when it comes to lifting towers"

***Gustav Barnard, Stage Audio Works, South Africa***

▷▷ "For years we have been happy with VMB towerlifts, they come with high security and the very best quality"

***Aculab Veranstaltungstechnik, Austria***

▷▷ "The motive for our decision to select VMB towerlifts was essentially for their quality, resistance and reliability, as well as assistance warranties provided by the brand/distributor. The decision was taken after comparing several products and brands, achieving the final conclusion that the best offer for price/quality was VMB. We acquired both TL-078B and TE-076P and are really satisfied with the equipment as well as the service provided by the VMB distributor in Portugal, Merging Select"

***João Pedro Flores, Corval Som, Portugal***

▷▷ "I just started last year to do professional service & hiring for lighting and audio equipment and it was pretty difficult to choose the right brand on the market. It had to be the best value for money and be tough enough for every day work. Now I can say I made the right decision when it came to VMB towerlifts. VMB will be my 1st choice for every future purchase without a doubt"

***Oliver Bilan, OLIVER SOUND&LIGHT, Croatia***

▷▷ "We have been using VMB towerlifts for over ten years now. Rigid construction, high load capacity, high reach and market acceptance are the keywords that brought us to VMB. They get the job done, every time, everywhere"

***Martijn van Thiel, Famous Music Entertainment, the Netherlands***



# technical specifications

## CLASSIC SERIES

	TE-034	TE-06
Maximum height	3,8 m	5 m
Maximum load	100 Kg	100 Kg
Work surface	1,5 x 1,5 m	2 x 2 m
Folded height	1,26 m	1,9 m
Weight	21 Kg	32 Kg
Winch	340 Kg	340 Kg
Adaptor	¿ 35 mm (PSU-06 / PSA-01)	¿ 35 mm (PSU-06 / PSA-01)

## PRO SERIES

	TE-064PRO	TE-071P	TE-074P	TE-076P
Maximum height	5,35 m	5,35 m	5,35 m	6,5 m
Maximum load	100 Kg	200 Kg	230 Kg	200 Kg
Security	ALS	ALS	ALS	ALS
Work surface	2 x 2 m	2,1 x 2,1 m	2,1 x 2,1 m	2,4 x 2,4 m
Folded height	1,72 m	1,73 m	1,74 m	1,83 m
Weight	41 Kg	71 Kg	91 Kg	95 Kg
Winch	340 Kg	500 Kg	650 Kg	650 Kg
Adaptor	¿ 35 mm	¿ 35 mm	¿ 55 mm	¿ 35 mm

For towerlift with 35 mm insertion use either PSU-06 or PSA-01.  
For towerlift with 55 mm insertion use either PSU-074 or PSA-02.

## TL SERIES

	TL-054	TL-055	TL-056	TL-072	TL-075C
Maximum height	5,45 m	5,1 m	6,5 m	6,5 m	6,5 m
Maximum load	220 Kg	220 Kg	200 Kg	240 Kg	300 Kg
Security	ILS	ILS	ILS	ALS	ALS
Work surface	2 x 2 m	2 x 2 m	2 x 2 m	2,2 x 2,2 m	2,2 x 2,2 m
Folded height	1,70 m	1,98 m	1,98 m	1,98 m	1,98 m
Weight	87 Kg	88,5 Kg	94,5 Kg	114 Kg	179 Kg
Winch	900 Kg	900 Kg	900 Kg	900 Kg	1200 Kg
Load support	Forks	Forks	Forks	Forks	Forks



## GS SERIES

	GROUND SUPPORT GS- 30	GROUND SUPPORT GS- 40
Maximum height	12 m	14 m
Maximum load	1500 Kg	3000 Kg
Elevation	1000 Kg CM hoist	2000 Kg CM hoist (2 chain falls)
Structure	Square 30 x 30 cm	Square 40 x 40 cm
Main bars	50 mm x 3,5 mm	50 mm x 3,5 mm
Braces	26 mm x 3,5 mm	26 mm x 3,5 mm

## PIRAM

	PIRAM 750	PIRAM 1000
Maximum load	750 Kg	1000 Kg
Maximum height	8 m	10 m
Structure	Triangular 25 cm	Square 30 cm
Base surface	3,22 x 3,22 m	3,62 x 3,62 m
Ground base	Articulated	Articulated
Material	Al 6082-T6	Al 6082-T6

VMB is continuously investigating and introducing innovations in order to improve the quality and the performance of its products. This is the reason why some characteristics described in this catalogue may change. A new product will always surpass the former model.

TL-078	TL-A220	TL-A320
8 m	5,5 m	6 m
280 Kg	220 Kg (0.5 m advanced)	320 Kg (0.5 m at distance)
ALS	ALS Auto-lock+Inertia ILS	ALS Auto-lock+Inertia ILS
2,2 x 2,2 m	2,78 x 2,78 m	2,25 x 2,15 m
1,98 m	1,72 m	1,98 m
203 Kg	95 Kg	184 Kg
1200 Kg	900 Kg	1200 Kg
Forks	Forks	Forks



CERTIFICATIONS  
 BGV C1 (GUV-VC1)  
 CE 89/392 EWG

Pat. n°:	2143360
Pat. n°:	6398445
Pat. n°:	989027461
Pat. Pen:	200501956



**TOWERLIFTRANGE**  
VMB ESPAÑOLA, S. A.

» Pol. Ind. Picassent · Final calle 2 · 46220 PICASSENT (VALENCIA) Spain  
Tel.: 902 34 10 34 · Intl Tel.: +34 961 22 15 21 · Fax: +34 961 22 11 77

[www.vmb.es](http://www.vmb.es) · [contact@vmb.es](mailto:contact@vmb.es)

